

7X Series 7.0 x 5.0 mm SMD Crystal

7 : 7.0×5.0×1.0 mm | SMD7050-4P

X : Crystal Resonator

Feature

- AT-cut Crystal Construction
- Ceramic surface mount with Metal Lid
- Package Size: 7.0 x 5.0 x 1.0mm
- Excellent heat resistance, high precision, and high reliability
- Pb-free and RoHS/Green compliant

Applications

- Industrial applications
- Portable devices
- Short-range Wireless module
- Computers, Modems, Microprocessors



Electrical Specifications

Item	Symb.	Min.	Typ.	Max.	Unit	Notes
Frequency Range	Freq.	6.000		50.000	MHz	
Oscillation Mode		Fundamental (AT-cut)				
Frequency Tolerance	$\Delta f/f$			± 10	ppm	at 25°C $\pm 2^\circ\text{C}$
Operating Temperature	T _{use}	-20		70	°C	
		-40		85	°C	
Storage Temperature Range	T _{sta}	-55		125	°C	
Shunt Capacitance	C ₀			5	pF	
Drive Level	DL		100	300	μW	
Load Capacitance	CL	8		20	pF	
Insulation Resistance	IR			500	M Ω	at DC 100V
Aging	f _{age}			3	ppm	1st. Year at 25°C

Frequency Stability & Operating Temperature Range

Temp. \ FT	$\pm 10\text{ppm}$	$\pm 15\text{ppm}$	$\pm 20\text{ppm}$	$\pm 30\text{ppm}$
-20°C to +70°C	$\triangle$	★	★	★
-40°C to +85°C		$\triangle$	★	★

★: Available $\triangle$: Conditional


Equivalent Series Resistance

Frequency Range	ESR(Max.)
6MHz $\leq$ Freq. < 8MHz	100 Ω
8MHz $\leq$ Freq. < 10MHz	60 Ω
10MHz $\leq$ Freq. < 14MHz	50 Ω
14MHz $\leq$ Freq. < 20MHz	40 Ω
20MHz $\leq$ Freq. $\leq$ 50MHz	30 Ω


7X Series 7.0 x 5.0 mm SMD Crystal

7 : 7.0×5.0×1.0 mm | SMD7050-4P X : Crystal Resonator

Dimensions (UNIT:mm)



Solder pad layout (UNIT:mm)



Options and Part Identification : Example SX7B6.000F1010F30

Company	Ceramic Package	Frequency Code [MHz]	Vibration Mode	Load Capacitance	Frequency Tolerance	Operating Temperature	Frequency Drift	
SX	7B	X.XXX	F	10	10	F	30	
		Frequency						
Code	Company	6.000	Code	Vibration Mode	Code	Frequency Tolerance	Code	Frequency Drift
SX	SCTF		F	AT - Fundamental	10	±10ppm	10	±10ppm
					20	±20ppm	15	±15ppm
							20	±20ppm
							30	±30ppm
						</		


If you have other parameter requirements, you can contact **SCTF** at any time.

7X Series 7.0 x 5.0 mm SMD Crystal

7 : 7.0×5.0×1.0 mm | SMD7050-4P

X : Crystal Resonator

Frequency Temperature Characteristics




Product Structure&Marking Information

Product Structure



Marking Information




7X Series 7.0 x 5.0 mm SMD Crystal

7 : 7.0×5.0×1.0 mm | SMD7050-4P

X : Crystal Resonator

Suggested Reflow Profile



Profile Feature	Sn - Pb Eutectic Assembly	Preheat / Soak
Preheat / Soak ● Temperature Min (T_{smin}) ● Temperature Max (T_{smax}) ● Time (T_{smin} to T_{smax})	100°C 150°C 60-120 seconds	150°C 200°C 60-120 seconds
Ramp - up rate (T_L to T_p)	3°C/ second max.	3°C/ second max.
Time maintained above ● Liquidous temperature (T_L) ● Time (t_L) maintained above T_L	183°C 60-150 seconds	217°C 60-150 seconds
Peak package body temperature (T_p)	235°C	260°C
Time within 5° C of the specified classification temperature (T_p)	20 seconds	30 seconds
Ramp - down rate (T_p to T_L)	6°C/ second max.	6°C/ second max.
Time 25° C to peak temperature	6 minutes max.	8 minutes max.
Suggest reflow times	2 Times max.	




7X Series 7.0 x 5.0 mm SMD Crystal

7 : 7.0×5.0×1.0 mm | SMD7050-4P

X : Crystal Resonator

Packaging Information

T=Tape and reel (1,000pcs/reel)



Pocket Tape Dimensions(mm)

Series	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
7X	0.3±0.05	7.5±0.1	1.8±0.1	16±0.3	7.5±0.1	5.5±0.1	8.0±0.1	4.0±0.1	2.0±0.1	φ1.5±0.1	2.0±0.2	4.0±1.0	φ13±0.5	φ60±1	φ180±1

Common Frequencies – MHz

7X Series				
6.000	6.144	7.3728	8.000	10.000
11.0592	12.000	12.288	14.31818	14.7456
16.000	16.384	19.6608	20.000	24.000
24.576	25.000	27.000	30.000	32.000
36.000	40.000	48.000		